

Android 10 OPS Pluggable machine



SKU:

EAN:

FEATUES

OPS pluggable Android 10 module, ARM ROCKCHIP soC encapsulation RK3399 CPU, 3x USB2.0, 1x USB3.0, RJ45.1,000M ethernet interface (optional dual ethernet interface) withTF card extension.Supports power-on boot, etc. Android 10.0 、 110SProducts meet CE/ FCC/ ROHS standard.



SPECIFICATIONS

Processor	CPU	ARM series ROCKCHIP RK3399
	Chipset	SOC
Memory	Capacity	4GB SO-DIMM DDR3 1600 MHz memory , Max.4GB
Storage	EMMC	32G, 64G, Max.128GB
	TF Card	Support 64G
Display	Graphics chip	CPU integrated HD Graphics HDMI
	Output	1 ×HDMI (Max. resolution : 3840x2160)
Function	MINI PCIE	1X MINI PCIE(3G/4G)
	COM interface	1X RS232
Ethernet	Lan	1 × 10/100/1000M (RJ45 LAN) IEEE 802.1X
	WIFI	1 × WIFI2.4G/5G dual mode +BT
I/O	USB 2.0	3x USB2.0 (Max. 3 pcs USB)
	USB 3.0	1x USB3.0
	Power button	1 × power button
	Reset	1 × upgrade
	OPS interface	1 × OPS interface (80pin)
	LED light	1 × LED light
	DC JACK Audio	1 × DC JACK
Power	Input	DC 12~19V
	Rated power	30W
Physical parameters	Dimensions	180mm (L) x 119mm (W)x30mm(H)
Environment	Temperature	Working temperature: 0°C ~50°C Storage temperature: -20~70°C
	Humidity	5%~90% No condensation
Operating system	Vision	Android10.0/11 / Linux